

## 2 1/2" (65 mm) Flow Test Kit with Case (High Flow Kit)

### STYLE AFTK-LK-KIT

AFTK-LK-KIT (High Flow) • Standard with 1 1/2", 1 3/4", 2", 2 1/4" & 2 1/2" (38, 44, 50, 57 & 65 mm) tips • 3 1/2" (89 mm) liquid filled 0-160 psi (0-1100 kpa) gauge • Large, heavy duty carrying case (FK-230), 18 3/8" W x 14 1/4" D x 8" H • 2 1/2" NH (65 mm) female swivel - Standard • Certified calibrated gauges • Flow range: 25-1900 gpm (95-7200 lpm)

Former style: FK-25

### Features

AFTK-LK-KIT (High Flow) • Standard with 1 1/2", 1 3/4", 2", 2 1/4" & 2 1/2" (38, 44, 50, 57 & 65 mm) tips • 3 1/2" (89 mm) liquid filled 0-160 psi (0-1100 kpa) gauge • Large, heavy duty carrying case (FK-230), 18 3/8" W x 14 1/4" D x 8" H • 2 1/2" NH (65 mm) female swivel - Standard • Certified calibrated gauges • Flow range: 25-1900 gpm (95-7200 lpm)



### Specifications

Style	AFTK-LK-KIT
Type	Apparatus Flow Test Kit
Swivel Inlet	2 1/2" (65mm)
Width	18 3/8" (467)
Height	8" (203 mm)
Depth	14 1/4" (362 mm)

## 2 1/2" (65 mm) Flow Test Kit with Case (High Flow Kit)

STYLE AFTK-LK-KIT

