



Front Load Battery Door Smoke Alarm with Hush®

A premium choice for controlling false alarms.

Features:



• **Ionization Technology** – Better at detecting fast flaming fires.



 Battery Powered – 9V battery included. Easy installation – accessible without removing cover plate.



• **Test Button** – Tests circuitry and verifies alarm operation.



• Hush® Button – Quickly silences nuisance alarms.



- Front Loading Battery Door Change the battery without removing the alarm.
- Tamper Resistant Locks the battery door compartment, preventing the removal of batteries for continuous protection.
- Low Battery Indicator Warning chirp sounds when battery needs replacement.

Specifications:

6" x 6" x 1.7" deep Product dimensions: Colour / Case Pack White / 8 units Electrical Rating: 9V Battery Operated Audio Alarm: 85dB 40°F (4.4°C) to 100°F (37.8°C) Temperature Range: Up to 85% relative humidity **Humidity Range:** Sensor: Ionization Limited Warranty: 5 Year



0976CA














0.70lb

0-47871-05225-7

Weight: UPC:





Smoke Alarm with Hush®

Hush® feature ideal to silence nuisance alarm without removing the battery.

Never remove the batteries or disable a smoke alarm. Be safe and replace the batteries annually.



0916KCA



Features:



- **Ionization Technology** Better at detecting fast flaming fires.
- =
- Battery Powered 9V battery included. Easy installation no wiring required.



• **Test Button** – Tests circuitry and verifies alarm operation.



- Hush® Button Quickly silences nuisance alarms.
- Low Battery Indicator Warning chirp sounds when battery needs replacement.
- Special mounting bracket included Allows for fast installation.

Specifications:


Product dimensions:	6" x 6" x 1.5" deep
Colour / Case Pack	White / 8 units
Electrical Rating:	9V Battery Operated
Audio Alarm:	85dB
Temperature Range:	40°F (4.4°C) to 100°F (37.8°C)
Humidity Range:	Up to 85% relative humidity
Sensor:	Ionization
Limited Warranty:	5 Year
Weight:	0.40lb
UPC:	0-47871-40375-2













10 Year Tamper Resistant Smoke Alarm with Hush®

A tamper resistant smoke alarm is a by-law in certain municipalities. This unit is ideal for landlords.

0910CA / i9010CA



Features:



- Ionization Technology Better at detecting fast flaming fires.
- 10
- Battery Powered 10 year, sealed lithium batteries. No need to buy and replace batteries – simply replace unit.



- **Test Button** Tests circuitry and verifies alarm operation.
- *****5
- Hush® Button Quickly silences nuisance alarms.



- **Tamper Resistant** Locks to inhibit tampering with the alarm, preventing the removal of batteries for continuous protection.
- Special mounting bracket included Allows for fast installation.

Specifications:

Product dimensions:	6" x 6" x 1.5" deep	
Colour / Case Pack	White / 6 units	
Electrical Rating:	10 Year Lithium Battery	
Audio Alarm:	85dB	
Temperature Range:	40°F (4.4°C) to 100°F (37.8°C)	
Humidity Range:	Up to 85% relative humidity	
Sensor:	Ionization	
Limited Warranty:	10 Year	
Weight:	0.40lb	
UPC:	0-47871-90152-4	cecuria
















Dual Sensor Smoke Alarm

In 2000, there were 21,206 house fires in Canada resulting in 327 deaths and \$529.5 million dollars in property loss.

For maximum protection every home should install both sensor technologies.



PI9000CA



Features:



 Photoelectric Technology – Better at detecting slow smouldering fires.



• Ionization Technology – Better at detecting fast flaming fires.



• **Battery Powered** – 9V battery included. Easy installation – no wiring required.



• **Test Button** – Tests circuitry and verifies alarm operation.



• Hush® Button – Quickly silences nuisance alarms.

- Low Battery indicator Warning chirp sounds when battery needs replacement.
- Special mounting bracket included Allows for fast installation.

Chapitiantiana	
Specifications:	

Product dimensions:	6" x 6" x 1.5" deep
Colour / Case Pack:	White / 8 units
Electrical Rating:	9V Battery Operated
Audio Alarm:	85dB
Temperature Range:	40°F (4.4°C) to 100°F (37.8°C)
Humidity Range:	Up to 85% relative humidity
Sensor:	Ionization and Photoelectric
Limited Warranty:	5 Year
Weight:	0.60lb
UPC:	0-47871-00031-9









