

National Fire Equipment Ltd.

CE-950-1-FR - 14 1/2"w X 30"h X 4"d (Tub I.D.)

FIRE EXTINGUISHER CABINET FIRE RATED - 2" Radius TB Semi Recessed

STANDARD CONSTRUCTION FEATURES


- 2" Rounded Turnback (Adjustable Angles on Front)
- Full Glass Bubble Canopy 16 ga. Door w/ Full Length Piano Hinge
- Glass Size 10 3/4"w x 26 3/4"h x 3"d (Glass Opening 8 1/2" x 25")
- White Powder Coat Paint Finish
- Accommodates: a) 20lb Dry Chemical Fire Extinguisher (Strike First Model: SF-ABC1020)
 - b) 6L Class K (Strike First Model: SF-6LK)
 - c) 2.4 Gal. Pressure Water (Strike First Model: SF-PW250)
- Stainless Steel Paddle Latch
- Satin Coat Galvanized Exterior 22 ga. Tub w/ UL Type X Drywall Lining


Warnock Hersey International Test Report WHI-495-1534 2 hour vertical fire rated assembly



Installation:

- Min. Rough opening: 16 1 /2"w X 32"h X 4"d
- 4" wall depth required
- Installation Instructions are included with each cabinet






TOP

No.10 x 2 1/2" Self Tapping Mounting Screws Not Included



*1" Turnback shown in picture





CABINET SIDE 31 3/4" 2" Radius T.B.