

**BUILT TOUGH,
EASY TO
SERVICE**



STRIKE FIRST
FIRE EXTINGUISHERS



**WHEN
SECONDS
COUNT.**



NATIONAL FIRE EQUIPMENT LTD.
SERVICE, SOLUTIONS, INNOVATION

40 Edilcan Drive, Concord, ON., L4K 3S6

T: 905-761-6355 F: 905-761-6458

Toll Free: 1-800-267-8508

www.nationalfire.com



MULTI-PURPOSE
ABC DRY CHEMICAL



6 YEAR WARRANTY



A



B



C

- Steel cylinder
- Super durable polyester powder paint finish with superior corrosion resistance
- Waterproof stainless steel gauge
- Handle reinforced, full grip hardcoat anodized aluminum
- Oversized pull pin with retaining strap for easier and faster activation
- Color and bar coded labels for accurate service
- Complies with NFPA 10 Standard
- Meets D.O.T. Requirements
- U.S.C.G. approved with bracket listed on label
- Temperature range: -65°F to 120°F (-54°C to 49°C)



LISTED

MEETS OR EXCEEDS
ANSI/UL 299 & 711



LISTED HOMOLOGUE

MEETS OR EXCEEDS
CAN/ULC-S504 & S508

CAPACITY	2.5 lbs.	5 lbs.	5 lbs.	10 lbs.	20 lbs.	30 lbs.
Model No.	ABC-025VWD	ABC-050WWD	ABC-050WWDL	ABC-100WWD	ABC-200WWD	ABC-300WWD
UL/ULC Rating	1-A : 10-B : C	3-A : 10-B : C	3-A : 40-B : C	6-A : 80-B : C	10-A : 120-B : C	10-A : 120-B : C



REGULAR
BC DRY CHEMICAL



6 YEAR WARRANTY



B



C

- Steel cylinder
- Super durable polyester powder paint finish with superior corrosion resistance
- Waterproof stainless steel gauge
- Handle reinforced, full grip hardcoat anodized aluminum
- Oversized pull pin with retaining strap for easier and faster activation
- Color and bar coded labels for accurate service
- Complies with NFPA 10 Standard
- Meets D.O.T. Requirements
- U.S.C.G. approved with bracket listed on label
- Temperature range: -65°F to 120°F (-54°C to 49°C)



LISTED

MEETS OR EXCEEDS
ANSI/UL 299 & 711



LISTED HOMOLOGUE

MEETS OR EXCEEDS
CAN/ULC-S504 & S508

CAPACITY	2.75 lbs.	5 lbs.	10 lbs.	20 lbs. (9.1 kg)
Model No.	PDC-025VWD	PDC-050WWD	PDC-100WWD	PDC-200WWD
UL/ULC Rating	10-B : C	10-B : C	60-B : C	80-B : C



CO₂
CARBON DIOXIDE



5 YEAR WARRANTY



B



C

- Well suited for corrosive environments
- Super durable polyester powder paint finish with superior corrosion resistance
- Industrial strength aluminum cylinder
- Stainless steel handles, pull pin and retaining chain
- Chrome plated solid brass valve
- Strong impact resistant horn
- Color and bar coded labels for accurate service
- Complies with NFPA 10 Standard
- D.O.T. approved cylinder
- U.S.C.G. approved with bracket listed on label
- Temperature range: -22°F to 120°F (-30°C to 49°C)



LISTED

MEETS OR EXCEEDS
ANSI/UL 154 & 711



LISTED HOMOLOGUE

MEETS OR EXCEEDS
CAN/ULC-S503 & S508

CAPACITY	5 lbs	10 lbs	15 lbs	20 lbs
Model No.	C02-050WW	C02-100WW	C02-150WW	C02-200WW
UL/ULC Rating	5-B : C	10-B : C	10-B : C	10-B : C



WATER



5 YEAR WARRANTY



A

- Polished stainless steel cylinder complete with protective skirt
- Chrome-plated solid brass valve
- Waterproof stainless steel gauge
- Stainless steel handles and siphon tube
- Oversized stainless steel pull pin with retaining strap for easier and faster activation
- Color and bar-coded labels for accurate service
- Shipped empty without pressure
- Schrader valve for pressurizing
- Complies with NFPA 10 Standard
- Meets D.O.T. Requirements
- Temperature range: 40°F to 120°F (4°C to 49°C)

CAPACITY	2.4 gallons (9 litres)
Model No.	PWS-250WWD
UL/ULC Rating	2-A



LISTED

MEETS OR EXCEEDS
ANSI/UL 626 & 711



LISTED HOMOLOGUÉ

MEETS OR EXCEEDS
CAN/ULC-S507 & S508



WET CHEMICAL



5 YEAR WARRANTY



A



K

- Polished stainless steel cylinder complete with protective skirt
- Chrome-plated solid brass valve
- Waterproof stainless steel gauge
- Stainless steel handles and siphon tube
- Oversized stainless steel pull pin with retaining strap for easier and faster activation
- Color and bar-coded labels for accurate service
- Factory filled and pressurized
- Complies with NFPA 10 Standard
- Meets D.O.T. Requirements
- Temperature range: 35°F to 120°F (2°C to 49°C)

CAPACITY	1.6 gallons (6 litres)
Model No.	CLASSK-6LWWD
UL/ULC Rating	1-A : K



LISTED

MEETS OR EXCEEDS
ANSI/UL 8 & 711



LISTED HOMOLOGUÉ

MEETS OR EXCEEDS
CAN/ULC-S554 & S508



DRY CHEMICAL

AUTOMATIC HEAT ACTUATED MULTI-PURPOSE



A



B



C

- Steel cylinder complete with protective skirt
- Super durable polyester powder paint finish with superior corrosion resistance
- UL Listed Heat Activated Sprinkler Head, rated at 165 degrees F (74° Celsius)
- Meets D.O.T. Requirements
- Designed to provide supplementary fire protection
- Available in two mounting styles: horizontal and vertical (Brackets available separately)
- Disposable unit, does not require maintenance and inspection at 6 or 12 years
- Typical installation locations: specific fire risk areas such as flammable liquid storage rooms, construction trailers and manufacturing process areas i.e. paint booths

CAPACITY	2.5 lbs (1.13 kg)	5 lbs (2.3 kg)	10 lbs (4.5 kg)	20 lbs (9.1 kg)
Model No.	AFE-025ABCV	AFE-050ABCV	AFE-100ABCV	AFE-200ABCV
	AFE-025ABCH	AFE-050ABCH	AFE-100ABCH	AFE-200ABCH



FIRE EXTINGUISHER CLASS LEGEND:



A

WOOD,
PAPER,
CLOTH



B

FLAMMABLE
LIQUIDS
& GASES



C

ELECTRICAL
EQUIPMENT



K

RESTAURANT,
KITCHEN HAZARD



STANDARD DUTY

MODEL	UP2, UP2 – DB	UB5, UB5 – DB
For Extinguisher	2.5 lb Dry Chemical	5 lb Dry Chemical
U.S.C.G. Approved	YES	YES

- Durable polyester powder paint finish
- Stainless steel strap and clips
- Durable rubber bumpers



MEDIUM DUTY

MODEL	UP10 – MD	UP5 – MD
Diameter	5 1/8" (13 cm)	4 1/4" (11 cm)
For Extinguisher	10 lb Dry Chemical	5 lb Dry Chemical
U.S.C.G. Approved	YES	YES

- Durable polyester powder paint finish
- Heavy gauge steel construction
- Compact design
- Ideal for forklifts, industrial trucks and delivery vehicles
- Double Strap Available



HEAVY DUTY

MODEL	HDVB-1	HDVB-2	HDVB-3	HDVB-4
Diameter	4 – 4 3/4" (102 – 121 cm)	5 – 6" (127 – 152 cm)	6 1/4 – 7 1/8" (159 – 181 cm)	6 1/4 – 7 1/8" (159 – 181 cm)
For Extinguisher	5 lb ABC/BC	10 lb ABC/BC	20 lb ABC/BC	30 lb ABC
		5 lb CO ₂	10 lb CO ₂ 15 lb CO ₂	
U.S.C.G. Approved	YES	YES	YES	YES

- Strong Uni-Body Construction
- Reflective label for added safety
- Stainless steel pull pin with tether
- Rounded corners for added safety
- Durable polyester powder coat finish
- Individually boxed for easy handling

WALL HOOKS



TYPE	PART NO.	FOR MODEL(S)
Dry Chemical	C160739	5 lb (ABC/BC)
	C160753	10 lb (ABC/BC)
	C160793	20 lb (ABC/BC)
	C160794	30 lb (ABC/DC)
CO ₂	SF5WH	5 lb (CO ₂)
	SF1015WH	10 lb (CO ₂)
		15 lb (CO ₂)
SF20WH	20 lb (CO ₂)	
Class K Water	W160600	Class K (6L)
		Water (2.4 gal/9L)

- Heavy gauge steel construction
- Designed for easy removal of fire extinguisher
- Durable polyester powder coat finish
- Universal design



EXTINGUISHER CART



MODEL	CAPACITY	HEIGHT	WIDTH	DEPTH	WEIGHT
HD-CART	7 – 8" Diameter	39" (99 cm)	13 1/4" (34 cm)	13 1/2" (8.2 cm)	20 lb (9 kg)



Shown with 30 lb ABC