



National Fire Equipment Ltd.

FIRE DEPARTMENT CONNECTONS DOUBLE INLET

Model 201, 2 1/2" (65mm) Siamese FD Connection – Straight
Model 202, 2 1/2" (65mm) Siamese FD Connection – Angle

Application: Double Inlet FD connection with 500 GPM inlet capacity used to supplement water supply in standpipe or sprinkler systems. Body comes with a single swing clapper to prevent water from exiting the second inlet when not in use. Body standard with (2) 2 1/2" (65mm) swivel hose thread inlets c/w brass plugs or red aluminum break off caps. Base with 4" (100mm) or 6" (152mm) female NPT. Standard plate lettering is "Auto. Spkr.", "Standpipe" or combined "Auto. Spkr / Standpipe".

Construction: Cast brass body with red aluminum plate and caps.


Rated Pressure: 300 PSI /2068.50 kpa

Options: Satin Chrome, Polished Brass, Polished Chrome.

Approvals: ULC, UL, FM




Model 201



	Inches	mm
	4" x 2 1/2 "	102 x 65
A	8 5/8"	219
B	11 21/32"	296

Model Number 201



	Inches	mm
	4" x 2 1/2 "	102 x 65
A	8 5/64"	205
B	11 11/16"	170
Depth	4 29/32"	125

Model Number 202

Model Number 201-G & 202-G. As above but with 4" (100mm) or 6" (152mm) grooved end.

Model 105, 2 1/2" (65mm) Double Clapper Siamese FD Connect – Straight
Model 106, 2 1/2" (65mm) Double Clapper Siamese FD Connect – Angle


Application: Double Inlet FD connections with a double swing clappers to prevent water from exiting the second inlet when not in use. Branding on body Standpipe or Auto. Spkr. Standard with (2) 2 1/2" (65mm) swivel hose thread inlet connections with 4" (100mm) or 6" (152mm) female NPT pipe main connection

Rated Pressure: 300 PSI /2068.50 kpa Options: Satin Chrome, Polished Brass, Polished Chrome.

Approvals: UL, FM




Model 106



A105	Inches	mm
	4" x 2 1/2 "	102 x 65
A	8 5/8"	219
B	11 21/32"	296

Model Number 105



A106	Inches	mm
	4" x 2 1/2"	102 x 65
A	10 1/8"	257
B	11 13/16"	300

Model Number 106

Model Number 105-G & 106-G. As above but with 4" (100mm) or 6" (152mm) grooved end.