


FIRE DEPARTMENT CONNECTONS OUTLET

Model 153, 1¹/₂" (38mm) Outlet Connection




Application: Single outlet connection used as a wall hydrant or small pump test connection. Compete with $1\frac{1}{2}$ " (38mm) NPT female x $1\frac{1}{2}$ " (38mm) male hose thread adapter, brass cap & chain and brass or red aluminum escutcheon plate. Lettering "Wall Hydrant" or "Pump Test"

Rated Pressure: 300 PSI /2068.50 kpa

Options: Brass and Chrome. Also available with polished finish.

Model 284, 2¹/₂" (65mm) Outlet Connection



Application: Single outlet connection used as a wall hydrant or pump test connection. Compete with $2\frac{1}{2}$ " (65mm) NPT female x $2\frac{1}{2}$ " (65mm) male hose thread adapter, brass cap & chain and brass or red aluminum escutcheon plate. Lettering "Wall Hydrant" or "Pump Test"


Rated Pressure: 300 PSI /2068.50 kpa **Options:** Satin Chrome, Polished Brass, Polished Chrome.

Model Number 284-G. As above but with $2\frac{1}{2}$ " (65mm) grooved end connection.

Model 294, 2¹/₂" (65mm) Siamese Outlet Connection – Straight (Illustrated) Model 296, 2¹/₂" (65mm) Siamese Outlet Connection – Angle



Model 294



B-B-

	inches	mm
	$4^{"} \ge 2^{1/2}$	101 x 63
Α	4 ³ /4 ["]	121
В	6 ³ /4 ["]	171



Model Number 294-G & 296-G. With grooved end pipe main connection.

Application: Double outlet connection 4" (100mm) female NPT inlet with (2) 2½" (65mm) hose thread outlets, complete with brass caps and round brass or aluminum escutcheon plate. Lettering "Wall Hydrant" or "Pump Test".

6" Connection: Use A104 6"x 4" Bushing

Construction: Cast Brass Body, Brass or Aluminum escutcheon plate, aluminum break-off caps or brass plugs. **Rated Pressure:** 300 PSI /2068.50 kpa

Options: Satin Chrome, Polished Brass, Polished Chrome.



Model A53G

For Control Valves on 2½" (65mm) Connections Use NFE Model A53 or Model A53G See Page VAL-08 in this catalogue for more information.

40 Edilcan Drive, Concord, Ontario L4K 3S6 - Tel: (905) 761-6355 - Fax: (905) 761-6458 - 1-800-267-8508 website: www.nationalfire.com