



National Fire Equipment Ltd.

Fireline Accessories

GATED WYE(S)

Permits complete flow control when a hose line needs to be split into two lines or when two lines are combined into one hose.

FEMALE X (2) MALES

- 1" NH x 1" NH 626365
- 1" NPSH x 1" NPSH 626367
- 1 1/2" NH x 1 1/2" NH 626373*
- 1 1/2" NPSH x 1 1/2" NPSH 626377
- 1 1/2" Forged QC x 1 1/2" Forged QC 626383
- 2 1/2" BCT/AMA x 1 1/2" NPSH 626385
- 2 1/2" CSA x 1 1/2" NPSH 626387
- 2 1/2" N. Scotia Zone 1 x 1 1/2" NPSH 626390
- 2 1/2" NH x 1 1/2" NH 626393
- 2 1/2" QST x 1 1/2" NPSH 626395
- 2 1/2" WCT x 1 1/2" NPSH 626397



1" Female by two
1" Males

1.82 kg
4.00 lbs



1 1/2" Female by two
1 1/2" Males

1.83 kg
4.03 lbs



2 1/2" Female by two
1 1/2" Males

2.13 kg
4.69 lbs

*US Forestry Service Approved to Spec 5100-380c

Note: All the above gated wyes can have various adapters changed to meet your needs. Call customer service for more details.

HYDRO-WICK ROOT SOAKER

A heavy duty model designed for use with standard forestry fire pumps. Standard models are fitted with GHT swivel female threads for use with our Myti-Flo® 3/4" hose and waterthief. Designed to fight against reignition from underground hot spots. Penetrates soil to "wet-out" subterranean hot spots with it's high pressure nozzles. High pressure ball valve provided for flow control and shut-off. Foam handgrips 10 feet (3m) of coupled Myti-Flo® 3/4" hose included.



2.36 kg
5.19 lbs

626525