



MONITORS



2 1/2" Monitor Model MON 25-2

Weight	Height	Width
45lb	22"	13"
20kg	559mm	330mm

- 2 1/2" Waterway - 750 GPM
- 3" Waterway - 1200 GPM
- 4" Waterway - 2000 GPM
- Stainless Steel Discharge Tip
- Stainless Steel Ball Bearings
- Double Seal Swivels
- Zerk Fittings for Lubrication
- Red Epoxy Finish - Inside and out
- 360° Horizontal Travel
- 140° Vertical Travel
- Operates Easily at All Pressure Ranges
- Available in Carbon and Stainless Steel

Model 3529 - Hydrant Mount. (Not illustrated)

Outlet: 2 1/2" or 3" male NPT.

Inlet: 2 1/2" Swivel (requires adapter for provincial threads)

Red Epoxy Finish. For use with model BB0309-31 or C0342-31 Monitors.

Adjustable bracket designed to fit most hydrants.

Butterfly valves available for shut off and water control feature.

Weight: 35 lb Height: 18"



Model 3530 - Hydrant Mount (illustrated)

Outlet: 2 1/2" or 3" 150# ASA raised face flange.

Inlet: Swivel (requires adapter for provincial threads)

Red Epoxy Finish. For use with model BB0309-1 or C0342-1 Monitors.

Adjustable bracket designed to fit most hydrants.

Butterfly valves available for shut off and water control feature.

Weight: 39 lb Height: 18"



Model 500A - 350 or 500 GPM. 2 1/2" N.H. Aluminum Hard Anodized. 6 1/2" length. 4 1/2" lbs. (illustrated)

Model 500B - Same as 500A but cast brass. 9lbs.

Model 1000AGG - 500-750-1000 or 1250 GPM. 2 1/2" N.H. Aluminum Hard Anodized. 6 3/4" length, 4 1/2" lbs.

Model 1000BCG - Same as 1000ACG but cast brass. 12 lbs.

*Contact our local representative for approval drawings before ordering.

