




# National Fire Equipment Ltd.

## MODEL 076 CPVC TWO-HOLE STAND OFF STRAP

Fig. 76  
CPVC Two-Hole  
Stand Off Strap



**FUNCTION:** Designed to support CPVC pipe horizontally from the side or bottom of beam, or composite wood joists with a minimum of 3/8" web thickness. Fig. 076 can only be used as a guide on top of beam or on vertical piping. Fig. 076 may be installed onto wood using supplied fasteners or into, minimum 18 gauge, steel using two 1/4" X 1" tek type screws. Features flared edges to protect piping as it slides through the installed fitting.

**SIZE:** 3/4" (20) through 2" (50) CPVC pipe

**FINISH:** Pre-galvanized

**MATERIAL:** Carbon Steel

**APPROVALS:** Underwriters Laboratories listed for US and Canada

**ORDERING:** Specify pipe size and model number.

PIPE SIZE		A		B		D NOMINAL		MATERIAL SIZE		BOX QTY.	MAX SPACING		APPX. WT.	
											ft.	m.	lbs.	kg
3/4	(20)	2 9/16	(65.09)	4 1/4	(107.95)	1.050	(26.67)	20ga x 1 1/8	(.79 x 28.58)	100	5.5	(1.68)	12.10	(5.49)
1	(25)	2 13/16	(71.44)	4 1/2	(114.30)	1.315	(33.40)	20ga x 1 1/8	(.79 x 28.58)	100	6	(1.83)	12.80	(5.81)
1 1/4	(32)	3 3/16	(80.96)	4 5/8	(117.48)	1.660	(42.16)	20ga x 1 1/8	(.79 x 28.58)	100	6.5	(1.98)	14.10	(6.40)
1 1/2	(40)	3 7/16	(87.31)	5	(127.00)	1.900	(48.26)	20ga x 1 1/8	(.79 x 28.58)	100	7	(2.13)	15.20	(6.89)
2	(50)	3 7/8	(98.43)	5	(127.00)	2.375	(60.33)	20ga x 1 1/8	(.79 x 28.58)	100	8	(2.44)	16.40	(7.44)

20ga. = 0.035" nominal