




National Fire Equipment Ltd.

MODEL 077 CPVC TWO-HOLE SIDE MOUNT STRAP

Fig. 77
CPVC Two-Hole
Side Mount Strap



FUNCTION: Designed to support CPVC pipe horizontally from the side or bottom of beam. Fig. 077 can only be used as a guide on top of beam or on vertical piping. Fig. 077 also acts as a restrainer to prevent the thrust of a sprinkler head during activation when mounted on top of structure. Fig. 077 may be installed onto wood using supplied fasteners or into minimum 20 gauge, steel using two 1/4" X 1" tck type screws. Features flared edges to protect piping and retaining dimples to allow for easy installation onto PIPE.

SIZE: 3/4" (20) through 2" (50) CPVC pipe

FINISH: Pre-galvanized

MATERIAL: Carbon Steel

APPROVALS: Underwriters Laboratories listed for US and Canada

ORDERING: Specify pipe size and model number.

PIPE SIZE		A		B		C		D		MATERIAL SIZE		BOX QTY.	MAX SPACING		APPX. WT.	
													ft.	m.	lbs.	kg
3/4	(20)	3 1/16	(58.74)	1 7/8	(47.63)	1 11/16	(42.86)	1.050	(26.67)	20ga x 1 1/8	(.79 x 28.58)	100	5.5	(1.68)	8.50	(3.86)
1	(25)	3 3/8	(65.09)	2 3/16	(55.56)	1 15/16	(49.21)	1.315	(33.40)	20ga x 1 1/8	(.79 x 28.58)	100	6	(1.83)	9.40	(4.26)
1 1/4	(32)	3 3/4	(74.61)	2 1/2	(63.50)	2 5/6	(58.74)	1.660	(42.16)	20ga x 1 1/8	(.79 x 28.58)	100	6.5	(1.98)	10.40	(4.72)
1 1/2	(40)	4 1/8	(82.55)	2 13/16	(71.44)	2 5/8	(66.68)	1.900	(48.26)	20ga x 1 1/8	(.79 x 28.58)	100	7	(2.13)	11.30	(5.13)
2	(50)	4 3/8	(92.08)	3 1/4	(82.55)	3	(76.20)	2.375	(60.33)	20ga x 1 1/8	(.79 x 28.58)	100	8	(2.44)	13.20	(5.99)

20ga. = 0.035" nominal