

National Fire Equipment Ltd.

2-1/2" STATION MONITOR 750 GPM FP-750

SPECIFICATION

National Fire/ Fire Pro® station monitors were specifically designed to meet all requirements of municipal and petrochemical applications. The balanced flow single waterway design and precision machining on swivel joints reduces friction loss while improving stream and distance, and ensures ease of operation at all pressure/ flow ranges. Carbon Steel construction with 304 stainless steel swivels. Standard red polyester powder coating inside and out protect against corrosion.

Type 304 stainless steel ball bearings in joints ensure easy movement and reliable operation.

REGULARLY FURNISHED

- 360° horizontal and 120° vertical travel
- 2-1/2" Waterway
- Zerk fitting for lubrication
- · Low friction loss
- · Seamless carbon or stainless steel construction
- 750 GPM (2839 lpm)

PRODUCT OPTIONS

- o Gauge and Guard
- o Parallel Handle
- o Steering Wheel Handle
- o Drainage Provisions
- o Metric Flanges
- o Shut Off Valve


FINISHES:


o Customer Colors _____ (Specify)



FP2-750 Shown

Model	Inlet	Outlet	Weight
	In (mm)	In (mm)	Lbs (kg)
FP2-750	2-1/2" FLANGE	2-1/2"	45
	(64)	(64)	(20)
FP2(F/M)-750	2-1/2" NPT	2-1/2"	45
	(64)	(64)	(20)
FP3-750	3" FLANGE	2-1/2"	52
	(76)	(64)	(24)
FP3(F/M)-750	3" NPT	2-1/2"	52
	(76)	(64)	(24)
FP4-750	4" FLANGE	2-1/2"	52
	(102)	(64)	(24)





TORONTO: (905) 761-6355 Toll Free: (800) 267-8508

VANCOUVER: (604) 420-1131 Toll Free: (800)-667-2138

BURNABY: (604)-299-4498 www.nationalfire.com EDMONTON: (780) 455-3870 Toll Free: (888)-891-1008

CALGARY: (403) 236-5661

MONCTON: (506) 859-7277 Toll Free: (877) 816-3473

MISSISSAUGA: (905) 565-1385