



National Fire Equipment Ltd.

NOZZLES FOR HARD RUBBER HOSE



HRS032-PS-020-CH
HRS032-PS-025-CH



HRS032-PS-020-RD
HRS032-PS-025-RD



HRS057-PS-020-RD
HRS057-PS-025-RD



HRS050-GM-020-CH
HRS050-GM-025-CH



HRS039-GM-020-NA
HRS039-GM-025-NA



HRS065-GM-020-RD
HRS065-GM-025-RD

National Fire hose reel nozzles are designed, tested and approved to meet European Standard EN671-1 and Australian Standard AS 1221. Nylon and ABS material complies to ageing test in accordance to ISO4892-2.2. Throw range position at 0.6M 30° inclination, in accordance to EN671-1 Clause 10.4 Flowrate meets the equivalent nozzle diameter of 6mm in accordance to EN671-1.

Code No.	Setting	Material	Finishing	Inlet Size	Flowrate @ 30Psi (2.0 Bar)	Throwrange @ 30Psi
HRS065-GM-020-RD	Jet/Spray	Nylon/Brass	Red	3/4" (19mm)	27L/Min (Jet)	11.5M
HRS065-GM-025-RD	Jet/Spray	Nylon/Brass	Red	1" (25mm)	35L/Min (Jet)	11.5M
HRS057-PS-020-RD	Jet/Spray	Nylon	Red	3/4" (19mm)	27L/Min (Jet)	11.0M
HRS057-PS-025-RD	Jet/Spray	Nylon	Red	1" (25mm)	35L/Min (Jet)	11.0M
HRS032-PS-020-RD	Jet/Spray	ABS/Brass	Red	3/4" (19mm)	27L/Min (Jet)	11.0M
HRS032-PS-025-RD	Jet/Spray	ABS/Brass	Red	1" (25mm)	35L/Min (Jet)	11.0M
HRS032-PS-020CH	Jet/Spray	ABS/Brass	Chrome	3/4" (19mm)	27L/Min (Jet)	11.0M
HRS032-PS-025-CH	Jet/Spray	ABS/Brass	Chrome	1" (25mm)	35L/Min (Jet)	11.0M
HRS039-GM-020-NA	Jet/Spray	Brass	Natural	3/4" (19mm)	27L/Min (Jet)	11.0M
HRS039-GM-025-NA	Jet/Spray	Brass	Natural	1" (25mm)	35L/Min (Jet)	11.0M
HRS039-GM-020-CH	Jet/Spray	Brass	Chrome	3/4" (19mm)	27L/Min (Jet)	11.0M
HRS039-GM-025-CH	Jet/Spray	Brass	Chrome	1" (25mm)	32L/Min (Jet)	11.0M
HRS050-GM-020-CH	Jet	Brass	Chrome	3/4" (19mm)	27L/Min	11.0M
HRS050-GM-020-CH	Jet	Brass	Chrome	1" (25mm)	32L/Min	11.0M