



National Fire Equipment Ltd.

CARBON DIOXIDE

STRIKE FIRST CARBON DIOXIDE FIRE EXTINGUISHERS ARE DESIGNED FOR:



FLAMMABLE LIQUIDS & GASES

CLASS B



ELECTRICAL CONDUCTIVITY

CLASS C



5 YEAR WARRANTY

- Well suited for corrosive environments
- Super durable polyester powder paint finish with superior corrosion resistance
- Industrial strength aluminum cylinder
- Stainless steel handles, pull pin, retaining chain and hose band
- Chrome plated solid brass valve
- Strong impact resistant horn
- Color and bar coded labels for accurate service
- Complies with NFPA 10 Standard
- D.O.T. Approved Cylinder
- U.S.C.G. approved with bracket listed on label
- Temperature range: -22°F to 120°F (-30°C to 49°C)



LISTED

MEETS OR EXCEEDS:
ANSI/UL 154 & 711



LISTED
HOMOLOGUÉ

MEETS OR EXCEEDS:-
CAN/ULC-S503 & S508

CAPACITY	5 lbs	10 lbs.	15 lbs.	20 lbs.
Model No.	SF-5CO2A	SF-10CO2A	SF-15CO2	SF-20CO2
UL/ULC Rating	5-B : C	10-B : C	10-B : C	10-B : C
U.S.C.G. Approval	Type B:C Size I	Type B:C Size II	Type B:C Size II	-
Range	6-12 ft (2-2.5 m)	6-12 ft (2-2.5 m)	6-12 ft (2-2.5 m)	6-12 ft (2-2.5 m)
Discharge Time	10 sec	10 sec	15 sec	20 sec
Height	17 1/4" (44 cm)	19 3/4" (50.2 cm)	26 1/4" (66.7 cm)	26 1/4" (66.7 cm)
Width	8 1/2" (21.6 cm)	11 3/4" (30 cm)	11 3/4" (30 cm)	12" (30.5 cm)
Diameter	5 1/4" (13.3 cm)	7" (17.8 cm)	7" (17.8 cm)	8" (21 cm)
Weight	13 1/2 lb (6.12 kg)	28 lb (12.7 kg)	37 lb (12.3 kg)	48 1/8 lb (21.8 kg)
Standard Bracket	Wall	Wall	Wall	Wall
Optional Brackets	HDVB-2	HDVB-3	HDVB-3	-



National Fire
Equipment Ltd.

TORONTO: (905) 761-6355
Toll Free: (800) 267-8508

OTTAWA: (613) 723-6071

VANCOUVER: (604) 420-1131
Toll Free: (800)-667-2138

BURNABY: (604)-299-4498

EDMONTON: (780) 455-3870
Toll Free: (888)-891-1008

CALGARY: (403) 236-5661

MONCTON: (506) 859-7277
Toll Free: (877) 816-3473

MISSISSAUGA: (905) 565-1385

www.nationalfire.com