




## GATE AND WYE VALVES

### Model A53 Gate Valve 2½" (65mm), Female NPT x Male Hose Thread



	Inches	mm
A	5 5/32	131
B	9 19/64	236
C	4 11/32	110
D	2 17/64	58
E	1 57/64	48

**Application:** Used for standpipes, fire pumps and hydrants as a control shut off valve.

**Construction:** Forged brass body with red hand wheel, solid brass wedge disc with tapered seats.

Rated Pressure: 300 psi / 2069 kpa

**Approvals:** UL & FM

**Optional Finishes:**

A53B – Rough Brass

A53C- Rough Chrome

A53PB – Polished Brass

A53PC – Polished Chrome


Also available in 3" (76mm) x 2 ½" (65mm) size

Also available with "L" shaped speed crank handle

**WARNING: NOT DESIGNED FOR FIRE DEPARTMENT STANDPIPE VALVE**

Use Model A86 soft seated valves only for FDC Connections fire hose cabinets & standpipe risers.

### Model A53G Hydrant Gate Valve 2½" (65mm), Swivel Hose Thread Female x Male Hose Thread



	Inches	mm
A	5 5/32	131
B	9 19/64	236
C	5 13/64	132
D	2 17/64	58
E	1 57/64	48

**Application:** Used for standpipes, fire pumps and hydrants as a control shut off valve for swivel connection to source. Easy to install and remove in areas with space constraints.

**Construction:** Forged brass body with red hand wheel, solid brass wedge disc with tapered seats.

Rated Pressure: 300 psi / 2069 kpa

**Approvals:** UL & FM

**Optional Finishes:**

A53GB – Rough Brass

A53GC- Rough Chrome

A53GPB – Polished Brass


A53GPC – Polished Chrome

Also available with "L" shaped speed crank handle

**WARNING: NOT DESIGNED FOR FIRE DEPARTMENT STANDPIPE VALVE**

Use Model A86 soft seated valves only for FDC Connections fire hose cabinets & standpipe risers.

### Model A99 Gated Wye Valve, 2½" (65mm) Swivel Hose Thread x (2) 1½" (38mm) Male Hose Thread



	Inches	mm
A	4 13/32	131
B	5 35/64	141
C	6 7/64	155
D	8 15/64	209

**Application:** Used to split 2½" (65mm) supply line connection into two (2) 1½" gated outlets.

**Construction:** Cast brass body painted red with red rubber covered steel handles. Chrome plated swivel inlets. Chrome plated internal balls with Teflon seats.

**Testing:** A99 Gated Wyes are manufactured to ISO 9002 standards. All valves are pressure tested to 400 PSI during production.

### Model A300 Plain Wye Connector



**Application:** For dividing one supply line into two separate lines.

**Construction:** Available in cast brass or lightweight cast aluminium.

Female Hose Thread Inlet x (2) male hose thread outlets

**Available Sizes:**

1½" Inlet x (2) 1½"

2½" Inlet x (2) 1½"

2½" Inlet x (2) 2"

2½" Inlet x (2) 2½"

3" Inlet x (2) 1½"

3" Inlet x (2) 2½"

4" Inlet x (2) 2½"

6" Inlet x (2) 2½"