




# National Fire Equipment Ltd.

## 2 1/2" (65 mm) ANGLE AND GLOBE VALVES

### Model A55, Angle Valve 2 1/2" 65mm (female x female NPT outlet)



Inches	mm
<b>A</b> - 5 1/8"	130
<b>B</b> - 10 9/16"	260
<b>C</b> - 3 5/32"	80
<b>D</b> - 2 41/64"	67

**Application:** Used with 2 1/2" hose racks with nipple. Use double male adapter Model A88 to convert to male hose thread.

**Construction:** Forged Brass with red handwheel.

**Rated Pressure:** 300 psi / 2068.50 kpa.

**Approvals:** ULC (CE x589), UL (618R) FM Approved

**Optional Finishes:**


**A55B-25** - Rough Brass

**A55C-25** - Rough Chrome

**A55PB-25** - Polished Brass

**A55PC-25** - Polished Chrome

### Model A56, Angle Valve 2 1/2" 65mm (female x male outlet specify hose thread)



Inches	mm
<b>A</b> - 5 1/8"	130
<b>B</b> - 10 9/16"	260
<b>C</b> - 3 5/32"	80
<b>D</b> - 2 41/64"	67

**Application:** Fire Department outlet valve for Class I fire fighting.

**Construction:** Forged Brass with red handwheel.

**Rated Pressure:** 300 psi / 2068.50 kpa.

**Approvals:** ULC (CE x589), UL (618R) FM Approved

**Optional Finishes:**


**A56B-25** - Rough Brass

**A56C-25** - Rough Chrome

**A56PB-25** - Polished Brass

**A56PC-25** - Polished Chrome

### Model A85, Straight Globe Valve, 2 1/2" 65mm (female x female NPT outlet)



Inches	mm
<b>A</b> - 5 1/8"	130
<b>B</b> - 10 53/64"	275
<b>C</b> - 6 13/16"	173
<b>D</b> - 2 5/8"	67

**Application:** Used for back feed installations. Use double male adapter Model A88 to convert to male hose thread.

**Construction:** Forged Brass with red handwheel.

**Rated Pressure:** 300 psi / 2068.50 kpa.

**Optional Finishes:**


**A85B** - Rough Brass

**A85C** - Rough Chrome

**A85PB** - Polished Brass

**A85PC** - Polished Chrome

### Model A86, Straight Globe Valve, 2 1/2" 65mm (female x male outlet specify hose thread)



Inches	mm
<b>A</b> - 5 1/8"	130
<b>B</b> - 10 53/64"	275
<b>C</b> - 7 3/64"	179
<b>D</b> - 2 5/8"	67

**Application:** Fire Department outlet valve for backfeed installations. Class 1 Fires

**Construction:** Forged Brass with red handwheel.

**Rated Pressure:** 300 psi / 2068.50 kpa.

**Approvals:** ULC (CE x589), UL (618R) FM Approved

**Optional Finishes:**

**A86B** - Rough Brass

**A86C** - Rough Chrome

**A86PB** - Polished Brass

**A86PC** - Polished Chrome