



National Fire Equipment Dry Sprinkler Order Form

Date: _____
 Customer Name: _____
 Ship-To Address: _____

 PO Number: _____
 Order Placed By: _____
 Tag: _____

Customer Service Use Only	
Order Number:	_____
Customer Number:	_____
Ship to Number:	_____
Branch/ ISR Init:	_____
Date/Time Entered:	_____
Ack. Sent:	_____
Freight Terms:	_____

Tax Exempt # (If Applies) _____ ** must provide tax exempt cert
 Provide Quote Number for Special Pricing: _____
 Special Instructions: _____


Total Quantity:	_____
------------------------	-------

Please choose appropriate Part Number Configuration from Dry Sprinkler Configuration Worksheet and fill in below:

PART # **6** - - - - -

Std Rec Ext No

Dry Head Desc: _____ Escut Style:



**please list length in inches

Quantity	Length

Quantity	Length

Quantity	Length

Quantity	Length

Dry Head Cover Plate Choices				
Finish	135 deg	Qty	165 deg	Qty
Natural Brass	567921135		567921165	
Bright Brass	567922135		567922165	
Bright Chrome	567929135		567929165	
Brushed Chrome	567928135		567928165	
Flat White	567920135		567920165	
Bright White	567924135		567924165	
Off White	567925135		567925165	
Black	567926135		567926165	
Special Order	56792X135		56792X165	

Refer to your Tyco Tech Data for detailed product information

Dimension Listings		
DS-1:	DS-2:	DS-3:
STD - 2 1/2" - 48"	FLUSH - 2" - 48"	FLUSH - 1 1/4" - 45 1/4"
REC - 3 1/2" - 48"	REC - 2 3/4" - 48"	DEEP Pend - 1" - 44"
DEEP Pend- 1/2" - 46"	EXT'D - 0" - 45 1/4"	NO Escut - 5" - 48"
DEEP S/W - 1/2" - 45 3/4"	NO ESCUT - 5"-48"	
UPRIGHT - 5" - 48"	DS-C:	DS-1 EC S/W:
NO ESCUT - 5" - 48"	5" - 48"	2 1/2" - 48"

Authorized Signature: _____

Date: _____

By signing above, Customer acknowledges that all specifications, measurements and other details with respect to Customer's dry sprinkler order are the sole responsibility of Customer. Customer agrees that it must ensure the accuracy of all such specifications measurements and other details for each dry sprinkler order and that all requirements set forth in Tyco Fire Protection Products applicable dry sprinkler Technical Data Sheet are complied with. Customer understands that dry sprinklers are being custom made pursuant to information supplied by Customer and that **under no circumstances can dry sprinklers be cancelled once in production or can be returned.**



National Fire Equipment Ltd. - Dry Sprinkler Configuration Worksheet

Choose series, style, temperature, & finish from charts and enter information on Dry Sprinkler Order Form

DS-1

Series DS-1 Standard Coverage - STANDARD Response Pendent, Upright & Horizontal Sidewall			
PART NUMBER		60 - XX - X - X	
		TEMPERATURE	FINISH
96	PENDENT w/ STD Escutcheon		
93	PENDENT w/ DEEP Escutcheon	0 135° F / 57° C	1 BRASS / WHITE
97	PENDENT w/ STD Recessed Esc	1 155° F / 68° C	4 WHITE / WHITE
92	PENDENT w/o Escutcheon	2 175° F / 79° C	9 CHROME / CHROME
94	SIDEWALL w/ STD Escutcheon	3 200° F / 286° C	0 CHROME / WHITE
53	SIDEWALL w/ DEEP Escutcheon	4 286° F / 141° C	
54	SIDEWALL w/o Escutcheon	5 360° F / 182° C	
98	UPRIGHT w/o Escutcheon		

DS-1

Series DS-1 Standard Coverage - QUICK Response Pendent, Upright & Horizontal Sidewall			
PART NUMBER		60 - XX - X - X	
		TEMPERATURE	FINISH
36	PENDENT w/ STD Escutcheon		
33	PENDENT w/ DEEP Escutcheon	0 135° F / 57° C	1 BRASS / WHITE
37	PENDENT w/ STD Recessed Esc	1 155° F / 68° C	4 WHITE / WHITE
32	PENDENT w/o Escutcheon	2 175° F / 79° C	9 CHROME / CHROME
34	SIDEWALL w/ STD Escutcheon	3 200° F / 286° C	0 CHROME / WHITE
43	SIDEWALL w/ DEEP Escutcheon	4 286° F / 141° C	
44	SIDEWALL w/o Escutcheon	5 360° F / 182° C	
38	UPRIGHT w/o Escutcheon		

DS-1

Series DS-1 EXTENDED COVERAGE Horizontal Sidewall		
PART NUMBER		60 - XXX - X
ORIENTATION / TEMPERATURE	FINISH	
EC S / W QUICK RESPONSE - QR	1	BRASS / WHITE
350 135° F / 57° C	4	WHITE / WHITE
351 155° F / 68° C	9	CHROME / CHROME
EC S / W STANDARD RESP - SR	0	CHROME / WHITE
950 135° F / 57° C		
951 155° F / 68° C		

DIMENSION MINIMUM & MAXIMUMS

DS-1	STD ESC	2 1/2"	- 48"
	REC ESC	3 1/2"	- 48"
	DEEP Pend	1/2"	- 46"
	DEEP S / W	1/2"	- 45 3/4"
	UPRIGHT	5"	- 48"
	NO ESC	5"	- 48"
	EXT Cov S/W	2 1/2"	- 48"

DS-2

Series DS-2 Standard Coverage - STANDARD Response Pendent			
PART NUMBER		61 - XX - X - X	
		TEMPERATURE	FINISH
10	PENDENT w/ FLUSH Escutcheon		
11	PENDENT w/ STD Recessed Esc	0 135° F / 57° C	1 BRASS / WHITE
12	PENDENT w/ DEEP Escutcheon	1 155° F / 68° C	4 WHITE / WHITE
13	PENDENT w/o Escutcheon	2 175° F / 79° C	9 CHROME / CHROME
		3 200° F / 93° C	0 CHROME / WHITE
		4 286° F / 141° C	5 BRASS / BRASS
		* 286 N/A in Rec	

DS-2

Series DS-2 Standard Coverage - QUICK Response Pendent			
PART NUMBER		61 - XX - X - X	
		TEMPERATURE	FINISH
30	PENDENT w/ FLUSH Escutcheon		
31	PENDENT w/ STD Recessed Esc	0 135° F / 57° C	1 BRASS / WHITE
32	PENDENT w/ DEEP Escutcheon	1 155° F / 68° C	4 WHITE / WHITE
35	PENDENT w/o Escutcheon	2 175° F / 79° C	9 CHROME / CHROME
		3 200° F / 93° C	0 CHROME / WHITE
		4 286° F / 141° C	5 BRASS / BRASS
		* 286 N/A in Rec	

DS-2

Series DS-2 EXTENDED Coverage - QR & SR Response Pendent			
PART NUMBER		61 - XX - X - X	
		TEMPERATURE	FINISH
40	PENDENT w/ FLUSH Escutcheon		
41	PENDENT w/ STD Recessed Esc	0 135° F / 57° C	1 BRASS / WHITE
42	PENDENT w/ DEEP Escutcheon	1 155° F / 68° C	4 WHITE / WHITE
43	PENDENT w/o Escutcheon	2 175° F / 79° C	9 CHROME / CHROME
		3 200° F / 93° C	0 CHROME / WHITE
		4 286° F / 141° C	5 BRASS / BRASS
		* 286 N/A in Rec	

DS-2	FLUSH	2"	- 48"
	REC ESC	2 3/4"	- 48"
	DEEP Pend	0"	- 45 1/4"
	NO ESC	5"	- 48"



DS-3

Series DS-3 EXTENDED COVERAGE STD Response Ordinary Hazard - Horizontal Sidewall (ECOH)	
PART NUMBER 61 - XXX - X	
ORIENTATION / TEMPERATURE	FINISH
FLUSH ESCUTCHEON	1 BRASS / BRASS
161 155° F / 68° C	4 WHITE / WHITE
163 200° F / 93° C	9 CHROME / CHROME
EXTENDED ESCUTCHEON	0 CHROME / WHITE
171 155° F / 68° C	
173 200° F / 93° C	
WITHOUT ESCUTCHEON	
151 155° F / 68° C	
153 200° F / 93° C	

DS-C

Series DS-C Dry Concealed	
PART NUMBER 60-XXX-1	
STANDARD RESPONSE	X
60 - 86 X - 1	TEMPERATURE
QUICK RESPONSE	1 155° F / 68° C
60 - 46 X - 1	3 200° F / 93° C
EXT COVERAGE - QR	
60 - 45 X - 1	

DIMENSIONS MINIMUM & MAXIMUMS

DS-3	FLUSH	2 1/4" - 45 1/4"
	DEEP Pend	1" - 44"
	NO ESC	5" - 48"
DS-C	FLUSH	5" - 48"

COVER PLATES

FINISH	135 DEG	165 DEG
Natural Brass	567 921 135	567 921 165
Bright Brass	567 922 135	567 922 165
Bright Chrome	567 929 135	567 929 165
Brushed Chrome	567 928 135	567 928 165
Flat White	567 920 135	567 920 165
Bright White	567 924 135	567 924 165
Off White	567 925 135	567 925 165
Black	567 926 135	567 926 165
Special Order	567 92X 135	567 92X 165

Reminder:

135 degree plates go with 155 degree heads
 165 degree plates go with 200 degree heads

LFII

Rapid Response Series LFII Dry-Type Residential Recessed Pendent Sprinklers (TY2235) Part Number Selection		
PART NUMBER 63 - XXX - X		
10 Pendent w / Recessed Escutcheon	TEMPERATURE	FINISH Sprk/Esc
	1 155° F / 68° C	2 BRASS/BRASS
	2 175° F / 79° C	4 WHITE/WHITE
		9 CHROME/CHROME

DIMENSION MINIMUM & MAXIMUMS

LFII	3-3/4" - 24"
-------------	--------------

Separately Ordered Escutcheon

Specify: Style 20 Recessed Escutcheon with (specify*) finish, P/N (specify*)

*Refer to Technical Data Sheet TFP770

LFII

Rapid Response Series LFII Dry-Type Residential Horizontal Sidewall Sprinklers (TY2235) Part Number Selection		
PART NUMBER 63 - XXX - X		
12 Horizontal Sidew all w / Recessed Escutcheon	TEMPERATURE	FINISH Sprk/Esc
13 Horizontal Sidew all w ithout Escutcheon	1 155° F / 68° C	2 BRASS/BRASS
		4 WHITE/WHITE
		9 CHROME/CHROME