

Walter Kidde Portable Equipment, Inc. encourages and expects you to read and understand the entire SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1.	IDENTIFICATION	
	Product Name	Badger Multi-Purpose ABC Dry Chemical Fire Extinguisher
	Other Names	Ammonium Phosphate, Monoammonium Phosphate, Multi-Purpose, ABC, Premium ABC - 90% MAP
	Recommended use of the chemical and	
	restrictions on use	
	Identified uses	Fire Extinguisher (re-chargeable and non-rechargeable)
	Restrictions on use	For firefighting use on Class A, B, C types of fires
	Company Identification	Walter Kidde Portable Equipment, Inc.
		1016 Corporate Park Drive
		Mebane, NC 27302
		USA
	Customer Information Number	(919) 563-5911
		(919) 304-8200
	Emergency Telephone Number	
	CHEMTREC Number	(800) 424-9300
		(703) 527-3887 (International)
	Issue Date	March 4, 2021
	Supersedes Date	December 10, 2019
		Distributed by/Distribuè par:
		Kidde Canada Inc.
		340 Four Valley Drive
		Vaughan, Ont L4K 5Z1
		800-565-1976

Safety Data Sheet prepared in accordance with OSHA's Hazard Communication Standard (29 CFR 1910.1200), the Canadian Hazardous Products Regulations (HPR) and the Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

2. HAZARD IDENTIFICATION

Hazard Classification

Gas under pressure – Compressed gas

Label Elements Hazard Symbols





Signal Word: Warning

Hazard Statements

Contents under pressure; may explode if heated.

Precautionary Statements Prevention

None

2. HAZARD IDENTIFICATION

Response

None **Storage** Protect from sunlight and store in well-ventilated place. Keep container tightly closed. **Disposal** None

Other Hazards

Rechargeable fire extinguishers as sold are charged with compressed air. When recharged with nitrogen as instructed, they present a simple asphyxiant hazard and exposure to nitrogen gas at high concentrations can cause suffocation by reducing oxygen available for breathing.

This product may contain trace quantities of quartz (crystalline silica) as an impurity. Prolonged exposure to respirable crystalline silica dust at concentrations exceeding the occupational exposure limits may increase the risk of developing a disabling lung disease known as silicosis. IARC has determined that Crystalline silica in the form of quartz or cristobalite dust is carcinogenic to humans (Group 1). To the best of our knowledge, it is unlikely that crystalline silica is above the concentration limit of 0.1% that would require classification.

Specific Concentration Limits

The values listed below represent the percentages of ingredients of unknown toxicity.

Acute oral toxicity	1 - 10%
Acute dermal toxicity	1 - 10%
Acute inhalation toxicity	1 - 10%
Acute aquatic toxicity	1 - 10%

3. COMPOSITION/INFORMATION ON INGREDIENTS

This product is a mixture.

Component	CAS Number	Concentration*
Calcium Carbonate	471-34-1	1 – 5%
Mica	12001-26-2	0.5 – 1.5%
Clay (Kaolin)	1332-58-7	0.1 – 1.0%
Non-hazardous ingredients Monoammonium Phosphate	7722-76-1	80 – 100%



Note: Pressurized extinguishers are sold using compressed air as the expellant. Rechargeable extinguishers are specified to be recharged with nitrogen.

*Exact concentration withheld as trade secret.

4. FIRST- AID MEASURES

Description of necessary first-aid measures

Eyes

Immediately flood the eye with plenty of water for several minutes, holding the eye open. Obtain medical attention if soreness or redness persists.

4. FIRST- AID MEASURES

Skin

Wash skin thoroughly with soap and water. Obtain medical attention if irritation persists. **Ingestion**

Dilute by drinking large quantities of water and obtain medical attention.

Inhalation

Move victim to fresh air. Obtain medical attention immediately for any breathing difficulty.

Most important symptoms/effects, acute and delayed

Aside from the information found under Description of necessary first aid measures (above) and Indication of immediate medical attention and special treatment needed, no additional symptoms and effects are anticipated.

Indication of immediate medical attention and special treatment needed Notes to Physicians

Treat symptomatically.

5. FIRE - FIGHTING MEASURES

Suitable Extinguishing Media

This preparation is used as an extinguishing agent and therefore is not a problem when trying to control a fire. Use extinguishing agent appropriate to other materials involved. Keep pressurized containers and surroundings cool with water spray as they may rupture or burst in the heat of a fire.

Specific hazards arising from the chemical

Pressurized containers may explode in heat of fire.

Special Protective Actions for Fire-Fighters

Wear full protective clothing and self-contained breathing apparatus as appropriate for specific fire conditions.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Wear appropriate protective clothing. Prevent skin and eye contact. Remove leaking container to a safe place. Ventilate the area.

Environmental Precautions

Prevent large quantities of the material from entering drains or watercourses.



Methods and materials for containment and cleaning up

Sweep up or vacuum and transfer into suitable containers for recovery or disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Wear appropriate protective clothing. Prevent skin and eye contact.

7. HANDLING AND STORAGE

Conditions for safe storage

Pressurized containers should be properly stored and secured to prevent falling or being knocked over. Do not drag, slide or roll pressurized containers. Do not drop pressurized containers or permit them to strike against each other. Never apply flame or localized heat directly to any part of the pressurized container. Store pressurized containers away from high heat sources. Storage area should be: - cool dry - well ventilated - under cover - out of direct sunlight

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits are listed below, if they exist.

Calcium Carbonate

OSHA PEL: 15 mg/m3 TWA, total dust 5 mg/m3 TWA, respirable fraction

Mica

ACGIH TLV: 0.1 mg/m3 TWA, measured as respirable fraction of the aerosol, containing <1% crystalline silica

OSHA PEL: 20 mppcf, <1% crystalline silica

Kaolin

ACGIH TLV: 2 mg/m3 TWA, for particulate matter containing no asbestos and <1% Crystalline silica OSHA PEL: 15 mg/m3 TWA, total dust

5 mg/m3 TWA, respirable fraction

Particulates not otherwise classified /regulated

OSHA PEL: 50 mppcf or 15 mg/m3 TWA, total dust

15 mppcf or 5 mg/m3 TWA, respirable fraction

Appropriate engineering controls

Engineering methods to prevent or control exposure are preferred. Methods include process or personnel enclosure, mechanical ventilation (dilution and local exhaust), and control of process conditions.

Individual protection measures Respiratory Protection

Wear respiratory protection if there is a risk of exposure. The specific respirator selected must be based on the airborne concentration found in the workplace and must not exceed the working limits of the respirator.

Skin Protection Gloves

Eve/Face Protection

Chemical goggles or safety glasses with side shields.



Body Protection Normal work wear.

9. PHYSICAL AND CHEMICAL PROPERTIES

<u>Agent</u>

Appearance

Physical State Solid (powder) Color Pale Yellow

9. PHYSICAL AND CHEMICAL PROPERTIES

Odor Odorless Odor Threshold No data available pН Not applicable Specific Gravity No data available Boiling Range/Point (°C/F) Not applicable Melting Point (°C/F) No data available Flash Point (PMCC) (°C/F) Not flammable Vapor Pressure No data available Evaporation Rate (BuAc=1) No data available Solubility in Water No data available Vapor Density (Air = 1) Not applicable VOC (g/l) None VOC (%) None Partition coefficient (n-No data available octanol/water) Viscosity No data available **Auto-ignition Temperature** No data available Decomposition Temperature No data available Upper explosive limit No data available Lower explosive limit No data available Flammability (solid, gas) No data available Expellant – Nitrogen (for recharged extinguishers) Appearance **Physical State** Compressed gas Color Colorless Odor None **Odor Threshold** No data available pН Not applicable **Relative Density** 0.075 lb/ft3 @70oF as vapor

Boiling Range/Point (°C/F) -196°C/-321°F Melting Point (°C/F) -210°C/-346°F Flash Point (PMCC) (°C/F) Not flammable Vapor Pressure No data available Evaporation Rate (BuAc=1) Not applicable Solubility in Water 0.02 g/L Vapor Density (Air = 1) 0.97 VOC (g/l) Not applicable **VOC (%)** Not applicable Partition coefficient (n-No data available octanol/water) Viscosity Not applicable



Auto-ignition Temperature Decomposition Temperature Upper explosive limit Lower explosive limit Flammability (solid, gas) No data available No data available Not explosive Not explosive Not flammable

10. STABILITY AND REACTIVITY

Reactivity

Pressurized containers may rupture or explode if exposed to heat.

Chemical Stability Stable under normal conditions.

Possibility of hazardous reactions Hazardous polymerization will not occur.

Conditions to Avoid Exposure to direct sunlight - contact with incompatible materials

Incompatible Materials Strong oxidizing agents - strong acids - sodium hypochlorite

Hazardous Decomposition Products Oxides of carbon - ammonia - oxides of phosphorus - nitrogen oxides

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Calcium Carbonate: Oral LD50 (Rat) >2000 mg/kg Dermal LD50 (Rabbit) >2000mg/kg Inhalation LC50(rat) >3.0mg/l <u>Mica:</u> Oral LD50 (Rat) >2000 mg/kg <u>Clay:</u> Oral LD50 (Rat) >5000 mg/kg Dermal LD50 (Rabbit) >5000mg/kg <u>Nitrogen</u> Simple asphyxiant

Specific Target Organ Toxicity (STOT) – single exposure

<u>Nitrogen:</u> Exposure to nitrogen gas at high concentrations can cause suffocation by reducing oxygen available for breathing. Breathing very high concentrations can cause dizziness, shortness of breath, unconsciousness or asphyxiation.

Specific Target Organ Toxicity (STOT) – repeat exposure

Calcium Carbonate: Available data indicates this component is not expected to cause target organ effects after repeat exposure.

Serious Eye damage/Irritation Calcium Carbonate: Not irritating (rabbit)



Mica: Not irritating (rabbit)

Skin Corrosion/Irritation

<u>Calcium Carbonate</u>: Not irritating (rabbit) <u>Mica:</u> Not irritating (rabbit)

11. TOXICOLOGICAL INFORMATION

Respiratory or Skin Sensitization

Calcium Carbonate: Non-sensitizing to skin in Mouse local lymph node assay.

Carcinogenicity

This product may contain trace quantities of quartz (crystalline silica) as an impurity. Prolonged exposure to respirable crystalline silica dust at concentrations exceeding the occupational exposure limits may increase the risk of developing a disabling lung disease known as silicosis. IARC has classified Silica Dust, Crystalline, in the form of quartz or cristobalite as 1 (carcinogenic to humans).

Germ Cell Mutagenicity

<u>Calcium Carbonate</u>: Negative results in the Mammalian Cell Gene Mutation Assay with and without metabolic activation, Ames test, and In vitro Mammalian Chromosome Aberration Test.

Reproductive Toxicity

No relevant studies identified.

Aspiration Hazard

Not an aspiration hazard.

12. ECOLOGICAL INFORMATION

Ecotoxicity

No relevant studies identified.

Mobility in soil

No relevant studies identified.

Persistence/Degradability

No relevant studies identified.

Bioaccumulative Potential

No relevant studies identified.

Other adverse effects

No relevant studies identified.

13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of container in accordance with all applicable local and national regulations.

14. TRANSPORT INFORMATION

DOT CFR 172.101 Data UN Proper Shipping Name Fire extinguishers, 2.2, UN1044 Fire extinguishers



UN Class UN Number UN Packaging Group Classification for AIR Transportation (IATA) (2.2) UN1044 Not applicable Consult current IATA Regulations prior to shipping by air.

14. TRANSPORT INFORMATION

Classification for Water Transport IMDG

Consult current IMDG Regulations prior to shipping by water.

When shipping via ground, portable fire extinguishers pressurized to less than 241 psi and of less than 1100 cubic inches in size meet the requirements of "Limited Quantity" as referenced in 49 CFR 173.309 (2010). There is no limited quantity designation for fire extinguishers when shipped by air or water.

This section is believed to be accurate at the time of preparation. It is not intended to be a complete statement or summary of the applicable laws, rules, or hazardous material regulations, and is subject to change. Users have the responsibility to confirm compliance with all laws, rules, and hazardous material regulations in effect at the time of shipping.

15. **REGULATORY INFORMATION**

United States TSCA Inventory

This product contains ingredients that are listed on or exempt from listing on the EPA Toxic Substance Control Act Chemical Substance Inventory.

Canada DSL Inventory

All ingredients in this product are listed on the Domestic Substance List (DSL) or the Non-Domestic Substance List (NDSL) or are exempt from listing.

SARA Title III Sect. 311/312 Categorization

Gas under pressure Simple asphyxiant (when recharged with nitrogen)

SARA Title III Sect. 313

This product does not contain any chemicals that are listed in Section 313 at or above de minimis concentrations.

16. OTHER INFORMATION

Legend

ACGIH: American Conference of Governmental Industrial Hygienists CAS#: Chemical Abstracts Service Number EC50: Effect Concentration 50% IARC: International Agency for Research on Cancer LC50: Lethal Concentration 50% LD50: Lethal Dose 50% N/A: Denotes no applicable information found or available OSHA: Occupational Safety and Health Administration PEL: Permissible Exposure Limit STEL: Short Term Exposure Limit TLV: Threshold Limit Value TSCA: Toxic Substance Control Act



Revision Date: March 4, 2021 Replaces: December 10, 2019 Changes made: Removal of non-pressurized product, revision to logo and company name.

16. OTHER INFORMATION

Information Source and References

This SDS is prepared by Hazard Communication Specialists based on information provided by internal company references.

Prepared By:

EnviroNet LLC.

The information and recommendations presented in this SDS are based on sources believed to be accurate. Walter Kidde Portable Equipment, Inc. assumes no liability for the accuracy or completeness of this information. It is the user's responsibility to determine the suitability of the material for their particular purposes. In particular, we make NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, with respect to such information, and we assume no liability resulting from its use. Users should ensure that any use or disposal of the material is in accordance with applicable Federal, State, and local laws and regulations.