

National Fire Equipment Ltd.

FIRE DEPARTMENT CONNECTONS SINGLE INLET

Model A190T, 11/2" (38mm) Residential FD Connection


Application: Single Inlet FD connection used to supplement water supply in residential sprinkler systems. 11/2" (38mm) hose thread swivel inlet x 11/2" (38mm) NPT Female. Complete with NPSH or NST swivel inlet, integral Auto. Spkr. Plate and plug with chain.

Construction: Cast Brass

Rated Pressure: 300 PSI /2068.50 kpa

	Inches	mm
	21/2 " x 3 "	38 x 38
Α	4 1/32"	110
В	1 61/64"	50
С	1 5/64"	27





Model A90C, 21/2" (65mm) x 3" (76mm) Single Inlet Connect with clapper


Application: Single Inlet FD connection with clapper checking device. 21/2" (65mm) hose thread swivel inlet x 3" (76mm) NPT female. Used to supplement water supply in buildings or zones where double inlet connections are too large.

Construction: Cast Brass

Rated Pressure: 300 PSI /2068.50 kpa

Approvals: UL Listed

	Inches	mm
	4" x 2 1/2 "	65 x 76
Α	6 29/32"	175
В	4 9/32"	109
С	2 7/32"	56



Model 196, 21/2" (65mm) Single Inlet Connection (Shown with red aluminum plate)


Application: Used as an FD connection to supplement building fire protection. Single Inlet connection c/w round escutcheon plate and brass plug and chain. 21/2" (65mm) hose thread swivel inlet x 21/2" (65mm) NPT Female. Model 196 NOT included with drop clappers. Standard lettering is "Auto. Spkr.", "Standpipe" or combined "Auto. Spkr / Standpipe".

Construction: Cast Brass Body and Plug with Aluminum or Brass Plate

Rated Pressure: 300 PSI /2068.50 kpa

Options: Red Aluminum Plate, Brass or Chrome.

Also available with polished finish



Model 196-G. As above but with grooved end pipe main connection