



**FIRE DEPARTMENT CONNECTONS SINGLE INLET**


**Model A190T, 1½” (38mm) Residential FD Connection**

**Application:** Single Inlet FD connection used to supplement water supply in residential sprinkler systems. 1½” (38mm) hose thread swivel inlet x 1½” (38mm) NPT Female. Complete with NPSH or NST swivel inlet, integral Auto. Spkr. Plate and plug with chain.

**Construction:** Cast Brass

**Rated Pressure:** 300 PSI /2068.50 kpa

	Inches	mm
	21/2 “ x 3 “	38 x 38
<b>A</b>	4 1/32”	110
<b>B</b>	1 61/64”	50
<b>C</b>	1 5/64”	27




**Model 196, 2½” (65mm) Single Inlet Connection**

(Shown with red aluminum plate)

**Application:** Used as an FD connection to supplement building fire protection. Single Inlet connection c/w round escutcheon plate and brass plug and chain. 2½” (65mm) hose thread swivel inlet x 2½” (65mm) NPT Female. Model 196 NOT included with drop clappers. Standard lettering is “Auto. Spkr.”, “Standpipe” or combined “Auto. Spkr / Standpipe”.

**Construction:** Cast Brass Body and Plug with Aluminum or Brass Plate

**Rated Pressure:** 300 PSI /2068.50 kpa



**Options:** Red Aluminum Plate, Brass or Chrome.  
Also available with polished finish

**Model 196-G.**

As above but with grooved end pipe main connection