







National Fire Equipment Ltd.

Fire Extinguisher Selection Sheet



As recommended by U.L. - Factory Mutual - N.F.P.A.

| Type | STD Dry Chemical Powder | A.B.C. Powder | Purple "K" Powder | Class K | Water Pressure | Carbon Dioxide | Halon 1211 |
|--|---|--|---|---|---|---|---|
| Paper - Cloth Wood - Rubbish Combustibles - ETC. | Surface Fires Only | Yes Excellent | Surface Fires Only | Yes | Yes Excellent | Surface Fires Only | Yes |
| Volatile Liquids Gas - Oil - Paint ETC. | Yes Excellent | Yes Excellent | Yes Excellent | NO | NO | Yes Excellent | Yes Excellent |
| Electrical Panels - Motors Apparatus ETC. | Yes Excellent | Yes Excellent | Yes Excellent | NO | NO | Yes Excellent | Yes Excellent |
| Commercial Deep Fat Fryers (cooking oil fires.) | NO | NO | NO | Yes Excellent | NO | NO | NO |
| Capacity | 2.75 LBS 5 LBS 10 LBS 20 LBS 30 LBS | 2.5 LBS 5 LBS 10 LBS 20 LBS 30 LBS | 5 LBS 10 LBS 20 LBS 30 LBS | 6L (1.59 gallons) | 2 GAL | 5 LBS 10 LBS 15 LBS 20 LBS | 1 LBS 3.5 LBS 7 LBS 17 LBS |
| Operating Method | Break Seal Pull Pin Squeeze Handle | Break Seal Pull Pin Squeeze Handle | Break Seal Pull Pin Squeeze Handle | Break Seal Pull Pin Squeeze Handle | Break Seal Pull Pin Squeeze Handle | Break Seal Pull Pin Squeeze Handle | Break Seal Pull Pin Squeeze Handle |
| Fire Fighting Agent | Standard Powder | All Purpose Powder | Purple "K" Powder | Potassium Acetate | Water | Carbon Dioxide | Halon 1211 |
| Approximate Horizontal Range | 5-20 ft | 5-20 ft | 5-20 ft | 2.4 m-3.7 m | 40-55 ft | 3-10 ft | 8-12 ft |
| Approximate Discharge Time | 8-25 Sec | 8-25 Sec | 8-25 Sec | 55-55 seconds | 1 Minutes | 8-30 Sec | 10-18 Sec |
| Hydrostatic Min Test Interval | See NFPA No. 10 | See NFPA No. 10 | See NFPA No. 10 | See NFPA No. 10 | See NFPA No. 10 | See NFPA No. 10 | See NFPA No. 10 |

| Label Symbols | Types of Fires |
|---|--|
| Class A  | For wood, paper, cloth trash and other ordinary combustibles. |
| Class B  | For gasoline, greases, oil, paints, and other flammable liquids. |
| Class C  | For live electrical equipment. Water will cause a danger of severe electrical shock. |
| Class K  | Commercial Deep Fat Fryers (cooking oil fires.) |

The label on the extinguishers shows one or more of the above symbols designating the types of fires on which should be used.

Pictographic operating instructions are shown on the label. Understand these before using the extinguisher.



TORONTO: (905) 761-6355
Toll Free: (800) 267-8508
OTTAWA: (613) 723-6071

VANCOUVER: (604) 420-1131
Toll Free: (800)-667-2138
BURNABY: (604)-299-4498
www.nationalfire.com

EDMONTON: (780) 455-3870
Toll Free: (888) 891-1008
CALGARY: (403) 236-6661

MONCTON: (506) 859-7277
Toll Free: (877) 816-3473
MISSISSAUGA: (905) 565-1385