



## PRESSURE REGULATING ANGLE VALVES

National Fire Equipment Ltd. regulating valves are designed to reduce pressures in standpipe systems under **flowing and non-flowing conditions** per NFPA standards for Class I, II and Class III Service. Commonly used for standpipe valve inlet pressures greater than 175 PSI (1207kPa), (Verify with local codes or authority have jurisdiction). All valves are standard with open/close visual indicators as well as optional supervisory switch brackets for valve monitoring.

NFE pressure regulating valves are also designed for use in fire sprinkler systems as zone control valves. Standard with automatic check valve function.

Valve supplied standard in top quality brass construction but also available in a variety of finishes in all hose threads.

### Model UR20 1½" (38mm) & 2½" (65mm) Female x Female Regulating Angle Valves.



**Application:** Used with Model HR type swing hose rack with nipple and lock nut. Can be installed in existing cabinets where standard angle valves are used.

**Constructed:** Forged Brass body with silver aluminium hand wheel.

**Rated Pressure:** 400 PSI / 2758 kPa.

**Approvals:** ULC and UL

**Optional Finishes:**

UR20-15NB - 1 1/2" (38mm) Rough Brass	UR20-25B - 2 1/2" (65mm) Rough Brass
UR20-15NC - 1 1/2" (38mm) Rough Chrome	UR20-25C - 2 1/2" (65mm) Rough Chrome
UR20-15NPB - 1 1/2" (38mm) Polished Brass	UR20-25PB - 2 1/2" (65mm) Polished Brass
UR20-15NPC - 1 1/2" (38mm) Polished Chrome	UR20-25PC - 2 1/2" (65mm) Polished Chrome

**NOTE:** UR20 & UR25 PR Valves are supplied factory set and are not field adjustable.

### Model UR25 1½" (38mm) & 2½" (65mm) Female x Male Regulating Angle Valves.



**Application:** Used with Model S-4 stationary pin racks, reels, trays and hangers for direct connection onto valve. Can be installed in existing cabinets where standard angle valves are used.

**Constructed:** Forged Brass body with silver aluminium hand wheel.



**Rated Pressure:** 400 PSI / 2758 kPa.

**Approvals:** ULC and UL

**Optional Finishes:**

UR25-15NB - 1½" (38mm) Rough Brass	UR25-25B - 2½" (65mm) Rough Brass
UR25-15NC - 1½" (38mm) Rough Chrome	UR25-25C - 2½" (65mm) Rough Chrome
UR25-15NPB - 1½" (38mm) Polished Brass	UR25-25PB - 2½" (65mm) Polished Brass
UR25-15NPC - 1½" (38mm) Polished Chrome	UR25-25PC - 2½" (65mm) Polished Chrome

**NOTE:** UR20 & UR25 PR Valves are supplied factory set and are not field adjustable.



	UR20 & UR25 1 1/2"	UR20 & UR25 2 1/2"
Approx.wt.	7½ lbs (3.4 kg)	18½ lbs (8.4 kg)
A MIN.	7¾" (197mm)	10 9/16" (268mm)
A MAX.	8¼" (210mm)	11 3/8" (289mm)
B	4" (102mm)	5" (127mm)
C	2½" (65mm)	3 5/8" (92mm)
D	3½" (89mm)	5 7/8" (149mm)
E	2 3/16" (56mm)	3¼" (83mm)
F	1 7/8" (48mm)	2 13/16" (71mm)

