



National Fire Equipment Ltd.

WICK® Si 300-10B VP



VALUE PROTECTION 3 STAGE HIGH PRESSURE FIRE PUMP

This pump is especially designed with value protection in mind offering such standard features as;


- Low pressure shut-off to protect the pump on loss of prime
- Remote fuel tank connection for extended run time
- Hand primer, poppet check valve and pressure gauge
- Electric start motor (battery not included)

Other features of this pump that make it the best performance 3 stage fire pump in it's class include the following;

- Exceeds US Federal pump performance requirements for Type 7 apparatus
- Most fuel efficient engine meeting type 7 requirements
- Powered by a 4 stroke, air cooled Briggs & Stratton Vanguard™ 10 HP overhead valve engine with over-speed protection
- Overhead valve design allows for cooler and cleaner runs, delivering more power, longer engine life, improved fuel economy and lower emissions
- Racing designed connecting rod and head gasket for increased torque and improved oil flow through the engine, maximizing internal component protection
- Forged crankshaft incorporating heat treated ball bearings to minimize friction and heat build-up
- Acoustically designed muffler for tonal quality and low noise level
- Can work in tandem at more than 400psi (28 Bar)
- Three stage foam compatible pump end
- Pump end and speed increaser can be rotated to multiple positions
- Anodized aluminum impellers and distributors
- Maintenance-free speed increaser
- Standard wraparound frame with folding handles
- 3 year manufacturer's warranty on the engine

WICK® Si 300-10B VP

Part#	Description
71WICKSI301-10VP-M	WICK® 4200-14B Pumper ..14 HP 4 Stroke Briggs & Stratton , 4 stage pump, Tubular frame for easy transportation. Value Protection model




Options

	Part#	Description
A	71W42-2715	Large Control Panel
B	70FLPFTXX	Fuel Tank .. see fuel section for complete listing
C	70FL15TPPS	Fuel line .. see fuel section for complete listing
C	70FL20TPPS	Thread protector 2" / 51mm
C	6124NM24PF	Thread protector 1 1/2" / 38mm
C1	6324PF24QCA	Thread protector 2" / 51mm
D	70FL20DLPS10	Draftlite HP suction hose .. 2"/51mm x 10'/3M c/w NPSH *
E	70FLFV2PF	Foot Valve / Strainer 2"/51mm NPSH Female *
F	70FLM15PF2NM10PM-A	Manifold 1 1/2"/38mm NH Male x 1 1/2"/38mm NPSH Swivel Female x 1 1/2"/38mm NH Male with 1"/25mm NPSH side port .. c/w caps **
G	70FLM15PF2NM10PM-B	Manifold 1 1/2"/38mm NH Male x 1 1/2"/38mm NH Male x 1 1/2"/38mm NPSH Swivel Female with 1"/25mm NPSH side port .. c/w caps **

*See website for complete listing of accessory and related products

WICK® SI300 PERFORMANCE



A Pressure in Bar **B** Pressure in PSI **C** Flow U.S. GPM
D Flow Liters / Min **E** Head Pressure Feet **F** Head Pressure Meters


WEIGHT & DIMENSIONS

Length	22.0"	55.9 cm
Width	18.75"	47.6 cm
Height	18.25"	46.4 cm
Weight (Dry) *	101 lbs.	45.8 kg
Suction	2.0"	50 mm NPSH
Discharge	1 1/2"	38 mm NPSH

ENGINE

Briggs and Stratton Vanguard™	Four Stroke
Power	10 HP gross @ 3600 RPM
Ignition	Magnetron electric ignition
Oil Capacity	28 Ounces / 0.8 Liters

Specifications subject to change without notice
 Vanguard™ is a trademark of Briggs and Stratton
 * Weight complete with frame and accessories as shown



TORONTO: (905) 761-6355
 Toll Free: (800) 267-8508
 OTTAWA: (613) 723-6071

VANCOUVER: (604) 420-1131
 Toll Free: (800)-667-2138
 BURNABY: (604)-299-4498

EDMONTON: (780) 455-3870
 Toll Free: (888)-891-1008
 CALGARY: (403) 236-5661

MONCTON: (506) 859-7277
 Toll Free: (877) 816-3473
 MISSISSAUGA: (905) 565-1385

www.nationalfire.com