



# National Fire Equipment Ltd.

## WATER MIST

**WATER MIST** is the ultimate extinguisher for Class A fires and for locations where a potential Class C (electrical) hazard exists. The fine spray from the unique misting nozzle provides safety from electrical shock, greatly enhances the cooling and soaking characteristics of the agent, and reduces scattering of burning materials. The Amerex Water Mist extinguishers contain de-ionized water (sold separately) making them the best extinguishers for protection of hospital environments, telecommunication facilities, and "clean room" manufacturing facilities. The Amerex Water Mist extinguishers are easy to use, maintain, and service.

### RUGGED

- 5-Year Manufacturer's Warranty
- Stored Pressure Design
- Stainless-Steel Cylinders
- Durable High-Gloss Polyester Powder Paint
- All-Metal Valve Construction
- Exclusive Crevice-Free, Butt-Welded Cylinder
- Temperature Range +40°F to 120°F

### MR CONDITIONAL

- Non-magnetic Construction Tested by an Independent Agency for use in MRI Facilities to 11.7 Tesla (including wall hanger bracket)

### CLEAN

- Non-toxic—Causes no Respiratory Problems
- 2-pack Charges 670 and 671 Deionized Water Extinguishing Agent Sold Separately
- Sanitary and Easy-to-Clean White Paint Finish
- No Powder Residue

### USER FRIENDLY

- Wand Provides Greatest Operator Safety
- Large Loop Stainless-Steel Pull Pin
- Maximum Visibility During Discharge
- No Electrical Conductivity Back to the Operator
- No Thermal or Static Shock
- Minimal Training—Simplest to use
- Most Economical Agent Available
- QR Coded and Bilingual Labels




B270

B272

### Recommended for Lithium-Ion Battery Fires

#### Tested to 11.7 Tesla

AGENT TYPE	DE-IONIZED WATER	
	B270	B272
MODEL NUMBER	B270	B272
UL & ULC RATING	2A:C	2A:C
CAPACITY	1.75 Gal	2.5 Gal
SHIPPING WT. (LBS. EMPTY)	7	8
HEIGHT (IN.)	19	24.5
HEIGHT WITH HOSE AND WAND INSTALLED (IN.)	24.5	27.5
WIDTH (IN.) 11 11	11	11
DEPTH (IN.) 7 7	7	7
RANGE (INITIAL-FT.) 10-12 10-12	10-12	10-12
DISCHARGE TIME (SEC.) 72 80	72	80
INCLUDED BRACKET NM Wall NM Wall	NM Wall	NM Wall
REQUIRED CHARGE MODEL 670 671	670	671



**MANUFACTURED AND TESTED TO ANSI/UL STANDARDS**  
 Complies with NFPA 10 Standard  
 ISO-9001 and ISO-14001 Certified  
 UL LISTED

**CONFORMS TO TEST STANDARDS:**  
 CAN/ULC-S554 - ANSI/UL8 &  
 CAN/ULC-S508 - ANSI/UL711